



Specifications

Model		EK3-471 (4WD)
Engine		
Model		E 3.276
Make		Escorts Ltd.
Number of cylinders		3
Gross output (Factory observed)	HP	47
Displacement	cc	2761
Rated RPM	rpm	2000
Fuel tank capacity	ℓ	60
Air cleaner		Dry
Transmission		
Gear		F8 / R8
Type		Partial Synchromesh
Clutch type		Double Clutch (H-PTO)
Brake type		Wet disk (OIB)
Max. traveling speed		
Forward	km/h	31.11
Reverse	km/h	31.08
PTO		
Speed	rpm	540/540E
Output	HP	38
Type		Independent
3-point hitch		Cat. I with Combine Ballends (Cat 2 & Cat1)
Steering		
		Power Steering
Hydraulics		
Control system		Draft & Position
Lift capacity (at lower link end)	kg	1530
Lift capacity (at 610mm behind lifting pt.)	kg	1060
Auxiliary valve		Standard
Tyre		
Front standard tyre		9.5 x 18
Rear standard tyre		14.9 x 28
Dimensions		
Overall length		3245
Overall width	mm	1800
Overall height	mm	2380 (From Muffler)
Wheel base	mm	1885
Ground clearance	mm	400 (Tie Rod)
Front tread width	mm	1524
Rear tread width	mm	1450
Turning radius w/o brake	mm	3.11
Tractor weight	kg	2210kg (with Carrier)

Standard attachment

Model name	EK3-471 (4WD)
Front weight	1 nos. x 42 Kg + 2 nos. x 22 Kg
Front weight bracket	Standard (80 kg)
Driver seat	Standard
Rear work light	Standard

* Kubota Corporation and ESCORTS LIMITED reserve the right to change the stated specifications without notice.

Optional attachment

Model name	EK3-471 (4WD)
Farmers kit	Standard
Rear tow hook	Fixed type
Wheel jack	Standard
Linkage draw bar	Optional
Tyre	
Front tyre (Option)	8. x 18
Rear tyre (Option)	13.6. x 28

EK

EK3-471 4WD DUAL PURPOSE TRACTOR

POWER. COMFORT. STYLE.



Manufactured by:

ESCORTS LIMITED

Marketed by:

KUBOTA Corporation

Distributed by: